

J-Series

Looking for high clarity and yet affordable solution, J-Series from V-KOOL Signature Range is the right choice for you!

J-Series Product Specifications

	J60	J70	J83
Visible Light Transmission	64.0%	68.0%	83.0%
Visible Light Reflectance (Glass)	7.0%	8.0%	7.0%
Visible Light Reflectance (Film)	11.0%	11.3%	9.0%
Ultraviolet Rejection	99.0%	99.0%	99.0%
Total Solar Energy Rejection	47.0%	44.0%	31.0%
Infra-Red Rejection	82.0%	72.0%	43.0%
Luminous Efficacy	1.06	1.01	1.01
Solar Heat Gain Coefficient	0.54	0.60	0.70
Shading Coefficient	0.62	0.66	0.80
U-Value (btu/h.ft2.F)	1.03	1.11	1.05
U-Value (W/m2.K)	5.85	6.28	5.94
Total Solar Transmission	38.4%	43.0%	60.5%
Glare Reduction	0.26	0.21	0.08
Total Solar Absorption	55.7%	50.0%	33.0%
Infrared Transmittance	19.0%	28.0%	57.0%



 $^{\circ}$ V-KOOL International Pte Ltd, 2006. This specification sheet is intended solely for reference and informational purpose only. As such, no part of this document may be extracted, duplicated or reproduced in any form otherwise for the stated intended purpose, without written permisson of its rightful owners.